

Moment obrotowy			2 Nm	5 Nm	10 Nm	20 Nm	2 Nm			5 Nm	10 Nm	20 Nm
Kod zaworu	DN	Kvs	2-drogowy, gwint wewnętrzny									
R404DK	10	0,3										
R405DK	10	0,4										
R406DK	10	0,63										
R407DK	10	1										
R408DK	10	1,6										
R409DK	10	2,5										
R412D	15	2,5	-				-					
R413D	15	4	-				-					
R414D	15	6,3	-				-					
R417D	20	6,3	-				-					
R418D	20	10	-				-					
R419D	20	16	-				-					

Współpraca z siłownikami, sterowanie analogowe

Sterowanie			Analogowe						
Zasilanie			24 V						
Typ siłownika			TR24-SR	LR24A-SR	LRC24A-SR	NR24A-SR	NRC24A-SR	SR24A-SR	
Moment obrotowy			2 Nm	5 Nm	5 Nm	10 Nm	10 Nm	20 Nm	
Kod zaworu	DN	Kvs	2-drogowy, gwint wewnętrzny						
R404DK	10	0,3							
R405DK	10	0,4							
R406DK	10	0,63							
R407DK	10	1							
R408DK	10	1,6							
R409DK	10	2,5							
R412D	15	2,5	-						
R413D	15	4	-						
R414D	15	6,3	-						
R417D	20	6,3	-						
R418D	20	10	-						
R419D	20	16	-						