



## CARBON DIOXIDE TRANSMITTERS CDT2000 DUCT SERIES



Multifunctional, duct mount CO<sub>2</sub> transmitters for building automation systems

The CDT2000 Duct series air quality transmitters are engineered for building automation systems in the HVAC/R industry. The CDT2000 Duct series measures carbon dioxide (CO<sub>2</sub>), utilizing the industry standard NDIR measurement principle, and temperature (T). Illuminated display ensures easy readability also from a distance. The CDT2000 Duct has a screwless lid and an easily adjustable mounting flange that make the installation of the device easy.

The CDT2000 Duct series transmitters calibrate themselves automatically using ABC™ logic. The ABC™ logic requires that the space in which the transmitter is used needs to be unoccupied for four hours per day so that the indoor CO<sub>2</sub> concentration drops to the outside level. CDT2000-DC Duct is a dual channel model with a measuring channel and a reference channel that makes a continuous comparison and the necessary adjustment accordingly. CDT2000-DC Duct is also suitable for buildings that are continuously occupied.



### CDT2000 Duct series devices include:

- Separate field configurable output for each measurement parameter (CO<sub>2</sub>, T)
- Mounting flange

### CDT2000 Duct series device options offer:

- Clear backlit display
- Modbus configuration

## APPLICATIONS

CDT2000 Duct series devices are commonly used to monitor:

- CO<sub>2</sub> levels of incoming and return air in ventilation system
- CDT2000-DC Duct series devices can also be used in applications where there is a constant source of carbon dioxide present (for example hospitals and greenhouses)

## MODEL SUMMARY

Description	CDT2000	
	Model	Product code
Carbon dioxide transmitter, duct mounted	CDT2000 Duct	302.001.001
- with display	CDT2000 Duct-D	302.001.002
- with Modbus configuration and display	CDT-MOD-2000 Duct-D	302.001.006
- with dual channel sensor	CDT2000-DC Duct	301.007.001
- with dual channel sensor and display	CDT2000-DC Duct-D	301.007.002
- with Modbus configuration, dual channel sensor and display	CDT-MOD-2000-DC Duct-D	301.007.003

# CARBON DIOXIDE TRANSMITTERS

## CDT2000 DUCT SERIES

### SPECIFICATIONS

#### Performance

##### Measurement ranges:

CO<sub>2</sub>: 400–2000 ppm  
Temperature: 0...50 °C

##### Accuracy:

CO<sub>2</sub>: ±40 ppm + 2 % of reading, DC model: 75 ppm or 10 % of reading (whichever is greater)  
Temperature: <0.5 °C

#### Technical Specifications

##### Media compatibility:

Dry air or non-aggressive gases

##### Measuring units:

ppm and °C

##### Measuring element:

CO<sub>2</sub>: Non-dispersive infrared (NDIR)  
Temperature: NTC10K

##### Calibration:

Automatic self-calibration ABC Logic™ or continuous comparison (DC)

##### Environment:

Operating temperature: 0...50 °C  
Storage temperature: -20...70 °C  
Humidity: 0 to 95 % rH, non condensing

#### Physical

##### Dimensions:

Case: 119 x 100 x 44.7 mm  
Probe: L=188 mm, d=12 mm

##### Mounting:

With flange, adjustable 0...188 mm

##### Weight:

150 g

##### Materials:

Case: ABS  
Cover: PC  
Probe: ABS

##### Protection standard:

IP54

##### Electrical connections:

4 spring loaded terminals  
(24 V, GND, CO<sub>2</sub>, T)  
0.2–1.5 mm<sup>2</sup> (12–24 AWG)

#### Electrical

Supply voltage: 24 VAC or VDC ±10 %  
Current consumption: max 230 mA (at 24 V) + 10 mA for each voltage output  
Output signals for every media: 0/2...5/10 VDC, Load R minimum 1 kΩ

#### Conformance

Meets requirements for CE marking:  
EMC Directive 2014/30/EU  
RoHS Directive 2011/65/EU  
WEEE Directive 2012/19/EU

COMPANY WITH  
MANAGEMENT SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 = ISO 14001 =



### HOW TO GENERATE A MODEL?

Example: CDT2000 Duct-D	Product series		
	CDT2000	Carbon dioxide transmitter, analog configurations	
	CDT-MOD-2000	Carbon dioxide transmitter, Modbus configuration	
	Calibration		
		ABC logic™, Automatic Background Calibration	
	-DC	Dual channel, for continuously occupied space	
	Mounting		
		Wall mount	
	Duct	Duct mount (not available with relay or relative humidity sensor)	
	Relay (only for wall mount model)		
	-1R	With relay	
		Without relay	
	Relative humidity sensor (only for wall mount model)		
	-rH	With relative humidity sensor	
	Without relative humidity sensor		
Display			
-D	With display		
	Without display		
Model	CDT2000	Duct	-D