

VVF22.25-2.5	Przelotowa	DN25	2,5	20	600	600	600	-
VVF22.25-4		DN25	4,0	20	600	600	600	-
VVF22.25-6.3		DN25	6,3	20	600	600	600	-
VVF22.25-10		DN25	10	20	600	600	600	-
VVF22.40-16		DN40	16	20	550	600	600	-
VVF22.40-25		DN40	25	20	550	600	600	-
VVF22.50-40		DN50	40	20	350	450	600	-
VVF22.65-63		DN65	63	20	200	250	600	-
VVF22.80-100		DN80	100	20	125	175	450	-
VVF22.100-160		DN100	160	40	-	-	-	300

Zawory trójdrogowe

Kod modelu	Konfiguracja	DN	Kvs [m ³ /h]	Skok nominalny (mm)	Ciśnienie rozwierające Δpmax [kPa]			
					SAX..	SKD..	SKB..	SKC..
VXF22.25-2.5	Trójdrogowa	DN25	2,5	20	300	300	300	-
VXF22.25-4		DN25	4,0	20	300	300	300	-
VXF22.25-6.3		DN25	6,3	20	300	300	300	-
VXF22.25-10		DN25	10	20	300	300	300	-
VXF22.40-16		DN40	16	20	300	300	300	-
VXF22.40-25		DN40	25	20	300	300	300	-
VXF22.50-40		DN50	40	20	300	300	300	-
VXF22.65-63		DN65	63	20	150	200	300	-
VXF22.80-100		DN80	100	20	75	125	300	-
VXF22.100-160		DN100	160	40	-	-	-	250